



## Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 11.03.2024

Revision: 11.03.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: FILLI BOYA SUPER ACRYLIC MATTE VARNISH HARDENER 8+1 AH 606**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture**
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Betek Boya ve Kimya Sanayi A.Ş.  
G.O.S.B. Tembelova Alani 3200 Sokak No:3206  
41400 Gebze/Kocaeli/Türkiye  
Tel: 00 90 262 678 30 00  
Fax: 00 90 262 641 21 68  
SeymaNur.Bektas@betek.com.tr
- **Further information obtainable from: R&D Department**
- **1.4 Emergency telephone number: 0090 262 678 30 00**

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Preparation date: 11.03.2024

Revision: 11.03.2024

Trade name: **FILLI BOYA SUPER ACRYLIC MATTE VARNISH HARDENER 8+1 AH 606**

(Contd. of page 1)

· **Hazard pictograms**

GHS02   GHS07   GHS08

· **Signal word** *Danger*· **Hazard-determining components of labelling:**

hexamethylene diisocyanate, oligomers

toluene

n-butyl acetate

xylene

· **Hazard statements**H225      *Highly flammable liquid and vapour.*H332      *Harmful if inhaled.*H315      *Causes skin irritation.*H317      *May cause an allergic skin reaction.*H361d      *Suspected of damaging the unborn child.*H335-H336 *May cause respiratory irritation. May cause drowsiness or dizziness.*H373      *May cause damage to organs through prolonged or repeated exposure.*H304      *May be fatal if swallowed and enters airways.*· **Precautionary statements**P101      *If medical advice is needed, have product container or label at hand.*P102      *Keep out of reach of children.*P103      *Read label before use.*P301+P310 *IF SWALLOWED: Immediately call a POISON CENTER/ doctor.*P321      *Specific treatment (see on this label).*P331      *Do NOT induce vomiting.*P303+P361+P353 *IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].*P362+P364 *Take off contaminated clothing and wash it before reuse.*P405      *Store locked up.*P501      *Dispose of contents/container in accordance with local/regional/national/international regulations.*· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**· **Description:**· **Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	25-50%
CAS: 28182-81-2	hexamethylene diisocyanate, oligomers ⚠ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	25-50%
CAS: 108-88-3 EINECS: 203-625-9	toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	10-25%

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Preparation date: 11.03.2024

Revision: 11.03.2024

**Trade name: FILLI BOYA SUPER ACRYLIC MATTE VARNISH HARDENER 8+1 AH 606**

(Contd. of page 2)

CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	2.5-10%
CAS: 1330-20-7 EINECS: 215-535-7	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-10%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

##### · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

##### · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

##### · After skin contact: Immediately wash with water and soap and rinse thoroughly.

##### · After eye contact: Rinse opened eye for several minutes under running water.

##### · After swallowing: If symptoms persist consult doctor.

#### · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

#### · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

#### · 5.1 Extinguishing media

##### · Suitable extinguishing agents:

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

#### · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

#### · 5.3 Advice for firefighters

##### · Protective equipment: Mouth respiratory protective device.

### SECTION 6: Accidental release measures

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

#### · 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

#### · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

#### · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Preparation date: 11.03.2024

Revision: 11.03.2024

**Trade name: FILLI BOYA SUPER ACRYLIC MATTE VARNISH HARDENER 8+1 AH 606**

See Section 13 for disposal information.

(Contd. of page 3)

### SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

#### · Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

#### · 7.2 Conditions for safe storage, including any incompatibilities

##### · Storage:

· Requirements to be met by storerooms and receptacles: Store in a cool location.

· Information about storage in one common storage facility: Not required.

##### · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

#### · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

· Additional information about design of technical facilities: No further data; see item 7.

#### · Ingredients with limit values that require monitoring at the workplace:

##### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppmLong-term value: 724 mg/m<sup>3</sup>, 150 ppm

##### 108-88-3 toluene

WEL Short-term value: 384 mg/m<sup>3</sup>, 100 ppmLong-term value: 191 mg/m<sup>3</sup>, 50 ppm

Sk

##### 108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppmLong-term value: 274 mg/m<sup>3</sup>, 50 ppm

Sk

##### 1330-20-7 xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppmLong-term value: 220 mg/m<sup>3</sup>, 50 ppm

Sk; BMGV

#### · Ingredients with biological limit values:

##### 1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 11.03.2024

Revision: 11.03.2024

Trade name: **FILLI BOYA SUPER ACRYLIC MATTE VARNISH HARDENER 8+1 AH 606**

(Contd. of page 4)

· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:**

Fluid

**Colour:**

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition****Melting point/freezing point:**

Undetermined.

**Initial boiling point and boiling range:** 110-111 °C· **Flash point:**

4 °C

· **Flammability (solid, gas):**

Not applicable.

· **Ignition temperature:**

315 °C

(Contd. on page 6)

# Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 11.03.2024

Revision: 11.03.2024

Trade name: **FILLI BOYA SUPER ACRYLIC MATTE VARNISH HARDENER 8+1 AH 606**

(Contd. of page 5)

· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto-ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
· <b>Vapour pressure at 20 °C:</b>	29 hPa
· <b>Density at 20 °C:</b>	0.9543 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not determined.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
Dynamic:	Not determined.
Kinematic:	Not determined.
· <b>9.2 Other information</b>	No further relevant information available.

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**  
Harmful if inhaled.

### · **LD/LC50 values relevant for classification:**

#### **108-88-3 toluene**

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Preparation date: 11.03.2024

Revision: 11.03.2024

**Trade name: FILLI BOYA SUPER ACRYLIC MATTE VARNISH HARDENER 8+1 AH 606**

(Contd. of page 6)

- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**  
Suspected of damaging the unborn child.
- **STOT-single exposure**  
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure**  
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

### SECTION 14: Transport information

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>· <b>14.1 UN-Number</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>                                | UN1263                                      |
| <ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG, IATA</b></li> </ul> | 1263 PAINT, special provision 640D<br>PAINT |

(Contd. on page 8)

GB



# Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 11.03.2024

Revision: 11.03.2024

**Trade name: FILLI BOYA SUPER ACRYLIC MATTE VARNISH HARDENER 8+1 AH 606**

(Contd. of page 7)

· **14.3 Transport hazard class(es)**

· **ADR**



- **Class** 3 (F1) Flammable liquids.  
 · **Label** 3

· **IMDG, IATA**



- **Class** 3 Flammable liquids.  
 · **Label** 3

· **14.4 Packing group**

- **ADR, IMDG, IATA** II

- **14.5 Environmental hazards:** Not applicable.

- **14.6 Special precautions for user** Warning: Flammable liquids.

- **Hazard identification number (Kemler code):** 33

- **EMS Number:** F-E,S-E

- **Stowage Category** B

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

- **Limited quantities (LQ)** 5L  
 · **Excepted quantities (EQ)** Code: E2  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 500 ml  
 · **Transport category** 2  
 · **Tunnel restriction code** D/E

· **IMDG**

- **Limited quantities (LQ)** 5L  
 · **Excepted quantities (EQ)** Code: E2  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 500 ml

- **UN "Model Regulation":** UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

## SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P5c** FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

(Contd. on page 9)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Preparation date: 11.03.2024

Revision: 11.03.2024

**Trade name: FILLI BOYA SUPER ACRYLIC MATTE VARNISH HARDENER 8+1 AH 606**

(Contd. of page 8)

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

#### · **Relevant phrases**

- H225 *Highly flammable liquid and vapour.*
- H226 *Flammable liquid and vapour.*
- H304 *May be fatal if swallowed and enters airways.*
- H312 *Harmful in contact with skin.*
- H315 *Causes skin irritation.*
- H317 *May cause an allergic skin reaction.*
- H332 *Harmful if inhaled.*
- H335 *May cause respiratory irritation.*
- H336 *May cause drowsiness or dizziness.*
- H361d *Suspected of damaging the unborn child.*
- H373 *May cause damage to organs through prolonged or repeated exposure.*

#### · **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- Repr. 2: Reproductive toxicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1