



Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 11.04.2023

Revision: 11.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** **FILLI BOYA FINE POLIURETAN MAT BOYA SERTLESTIRICI 2+1 EXPERT**
FILLI BOYA FINE POLYURETHANE MATTE PAINT HARDENER 2+1 EXPERT
FILLI BOYA ФИНЕ ПОЛИУРЕТАНОВЫЙ МАТОВАЯ КРАСКА ОТВЕРДИТЕЛЬ 2+1 EXPERT
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Betek Boya ve Kimya Sanayi A.Ş.
G.O.S.B. Tembelova Alani 3200 Sokak No:3206
41400 Gebze/Kocaeli/Türkiye
Tel: 00 90 262 678 30 00
Fax: 00 90 262 641 21 68
SeymaNur.Bektas@betek.com.tr
- **Further information obtainable from:** R&D Department
- **1.4 Emergency telephone number:** 0090 262 678 30 00

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Water-react. 1 H260 In contact with water releases flammable gases which may ignite spontaneously.



health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 11.04.2023

Revision: 11.04.2023

Trade name: FILLI BOYA FINE POLIURETAN MAT BOYA SERTLESTIRICI 2+1 EXPERT
FILLI BOYA FINE POLYURETHANE MATTE PAINT HARDENER 2+1 EXPERT
FILLI BOYA ФИНЕ ПОЛИУРЕТАНОВЫЙ МАТОВАЯ КРАСКА ОТВЕРДИТЕЛЬ 2+1 EXPERT

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

toluene

n-butyl acetate

· Hazard statements

H225 Highly flammable liquid and vapour.

H260 In contact with water releases flammable gases which may ignite spontaneously.

H315 Causes skin irritation.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P223 Do not allow contact with water.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description:

· Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	50-100%
CAS: 108-88-3 EINECS: 203-625-9	toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	10-25%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31



Preparation date: 11.04.2023

Revision: 11.04.2023

Trade name: FILLI BOYA FINE POLIURETAN MAT BOYA SERTLESTIRICI 2+1 EXPERT
FILLI BOYA FINE POLYURETHANE MATTE PAINT HARDENER 2+1 EXPERT
FILLI BOYA ФИНЕ ПОЛИУРЕТАНОВЫЙ МАТОВАЯ КРАСКА ОТВЕРДИТЕЛЬ 2+1 EXPERT

(Contd. of page 2)

CAS: 141-78-6 ethyl acetate

EINECS: 205-500-4  Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336

2.5-10%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately rinse with water.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

Extinguishing powder. Do not use water.

CO2. Do not use water.

Sand. Do not use water.

Special powder for metal fires. Do not use water.

CO2, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water

· 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

· 5.3 Advice for firefighters

· **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 11.04.2023

Revision: 11.04.2023

Trade name: FILLI BOYA FINE POLIURETAN MAT BOYA SERTLESTIRICI 2+1 EXPERT
FILLI BOYA FINE POLYURETHANE MATTE PAINT HARDENER 2+1 EXPERT
FILLI BOYA ФИНЕ ПОЛИУРЕТАНОВЫЙ МАТОВАЯ КРАСКА ОТВЕРДИТЕЛЬ 2+1 EXPERT

(Contd. of page 3)

6.4 Reference to other sections

See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Additional information about design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm
	Long-term value: 724 mg/m ³ , 150 ppm

108-88-3 toluene

WEL	Short-term value: 384 mg/m ³ , 100 ppm
	Long-term value: 191 mg/m ³ , 50 ppm
Sk	

141-78-6 ethyl acetate

WEL	Short-term value: 1468 mg/m ³ , 400 ppm
	Long-term value: 734 mg/m ³ , 200 ppm

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 11.04.2023

Revision: 11.04.2023

Trade name: FILLI BOYA FINE POLIURETAN MAT BOYA SERTLESTIRICI 2+1 EXPERT
FILLI BOYA FINE POLYURETHANE MATTE PAINT HARDENER 2+1 EXPERT
FILLI BOYA ФИНЕ ПОЛИУРЕТАНОВЫЙ МАТОВАЯ КРАСКА ОТВЕРДИТЕЛЬ 2+1 EXPERT

(Contd. of page 4)

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	77-78 °C

· **Flash point:** 4 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 460 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 11.04.2023

Revision: 11.04.2023

Trade name: FILLI BOYA FINE POLIURETAN MAT BOYA SERTLESTIRICI 2+1 EXPERT
FILLI BOYA FINE POLYURETHANE MATTE PAINT HARDENER 2+1 EXPERT
FILLI BOYA ФИНЕ ПОЛИУРЕТАНОВЫЙ МАТОВАЯ КРАСКА ОТВЕРДИТЕЛЬ 2+1 EXPERT

(Contd. of page 5)

· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
· Vapour pressure at 20 °C:	29 hPa
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not determined.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Contact with water releases flammable gases.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 11.04.2023

Revision: 11.04.2023

Trade name: FILLI BOYA FINE POLIURETAN MAT BOYA SERTLESTIRICI 2+1 EXPERT
FILLI BOYA FINE POLYURETHANE MATTE PAINT HARDENER 2+1 EXPERT
FILLI BOYA ФИНЕ ПОЛИУРЕТАНОВЫЙ МАТОВАЯ КРАСКА ОТВЕРДИТЕЛЬ 2+1 EXPERT

(Contd. of page 6)

584-84-9 4-methyl-m-phenylene diisocyanate

Oral	LD50	5,800 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**
Suspected of damaging the unborn child.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

GB

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31



Preparation date: 11.04.2023

Revision: 11.04.2023

Trade name: FILLI BOYA FINE POLIURETAN MAT BOYA SERTLESTIRICI 2+1 EXPERT
FILLI BOYA FINE POLYURETHANE MATTE PAINT HARDENER 2+1 EXPERT
FILLI BOYA ФИНЕ ПОЛИУРЕТАНОВЫЙ МАТОВАЯ КРАСКА ОТВЕРДИТЕЛЬ 2+1 EXPERT

(Contd. of page 7)

SECTION 14: Transport information

· 14.1 UN-Number	UN1263
· ADR, IMDG, IATA	
· 14.2 UN proper shipping name	1263 PAINT RELATED MATERIAL, special provision 640D
· ADR	PAINT RELATED MATERIAL
· IMDG, IATA	
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	339
· EMS Number:	F-E,S-E
· Stowage Category	B
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 11.04.2023

Revision: 11.04.2023

Trade name: FILLI BOYA FINE POLIURETAN MAT BOYA SERTLESTIRICI 2+1 EXPERT
FILLI BOYA FINE POLYURETHANE MATTE PAINT HARDENER 2+1 EXPERT
FILLI BOYA ФИНЕ ПОЛИУРЕТАНОВЫЙ МАТОВАЯ КРАСКА ОТВЕРДИТЕЛЬ 2+1 EXPERT

(Contd. of page 8)

· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, SPECIAL PROVISION 640D, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
O2 Substances and mixtures which in contact with water emit flammable gases
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
- **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Water-react. 1: Substances and mixtures which in contact with water emit flammable gases – Category 1
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1